

Data logger for various on-site measurements

PORTABLE DATA LOGGER TS-360

T-ZACCS 3

Control unit **TS-360**

T-ZACCS+

Battery unit **BA-360**

Driver unit **AU-50MA**

T-ZACCS UNIT

Channel unit **AU-10**

Channel unit **AU-10-05**

T-ZACCS+

Master unit **AU-50M**



Features

- Can be configured from small to large measurement systems
- LAN communication with remote measurement assistance function
- Low power consumption operation
- Measurement speed 0.08 sec/point
*0.2 sec/point when measured by TML-NET
- External switch box can connect up to 20 units,
1000 points, 2 km when booster power is turned on
- Channel unit AU-10/AU-10-05:
Color LED lights up when measuring
(Strain [red]/DC voltage [blue]/Thermocouple [green])

Point

1. Up to 1000 points
Number of measurement points
up to 50 points connected to the
main unit
External connection:
up to 1000 points total

**2. LAN interface
as standard**
Remote control is available!

3. TML-NET Compatible
100 units can be connected
with TML-NET

**4. Connection to
Switching box**

T-ZACCS BOX AU-50, ASW-50C,
and SSW-50D can be connected
as an external switching box!

**5. Battery-powered
operation**
Powered by 4 single batteries
or AC adapter (12V battery).

Application

—For example, you can do this!



Case
1.



Pavement

Point

TS-360 is battery-operated, making it powerful in places where there is no power supply!

Point

Connecting to an external switch box, up to 1000 points can be used, making it useful for multi-point field measurements!

Case
2.



Slope and mountain area

Point

"TML-NET" can be used. Therefore, it can be used at landslide and water level observation sites where measurement points are scattered

Point

Supports sleep interval measurement, ideal for unattended measurement using dry cell batteries or batteries at sites that are distant or difficult to access!

Case
3.



Bridge

Point

When used in connection with an external switch box, you can have the right number of points where you need them!

Point

TS-360 also supports online measurement by connecting I/F (LAN, USB, RS-232C)!

Case
4.



Tunnel

Point


TS-360 can increase the number of points and distribute placement as construction progresses!

Point

T-ZACCS BOX AU-50 can be connected as an external switch box. Existing switch box ASW-50C/SSW-50D can also be connected!

1 TML-NET Measurement System (Measurement by TML-NET interface on AU-50MA)

Measurements of 100 network modules are possible.
(200 points when 2-channel module is used)



2 External Switching box measurement system

T-ZACCS BOX AU-50 and conventional switching boxes ASW-50C /SSW-50D can be used (can be mixed)!


Capable of measuring up to 1000 points.

Sensor Input

- Strain gauge
- Strain gauge transducers
- Thermocouple
- DC voltage

*Only SSW-50D is capable of 1-gauge 4-wire measuring method

Total distance between data loggers and switch boxes not exceeding 2 km



System Block Diagram

TS-360



LAN / USB
RS-232C



PC /
Software



External Printer

TML-NET

T-ZACCS 3
PORTABLE
DATA LOGGER
TS-360

BA-360

TS-360

AU-50MA

AU-10-05

AU-10



*Up to five AU-10/AU-10-05 units can be connected to one AU-50MA unit

TS-360
AU-50MA
AU-10-05
AU-10



External Switching box

T-ZACCS 3 PORTABLE DATA LOGGER TS-360

T-ZACCS 3

Control unit TS-360



Measuring capacity

Number of measurement points		Up to 1000 points	
Measuring speed	Scanning measurement	0.080 sec/point (50Hz) 0.067 sec/point (60Hz)	
	Monitor measurement	0.5 sec/point	
Measurement mode		Initial, Direct, Major (Temperature measurement is direct only)	
Simple Measure		Coefficient	1
		Unit	Linked to sensor mode
		Decimal point	Linked to sensor mode
Comet setting		Comet NON, Comet A, Comet B	
Monitor	Display mode	OFF, numerical value, scan	
	Display channel	numeric representation	1 to 8 points
measurement	Manual Measurement	Scanning display	
	Automatic measurement interface	1 to 1000 points	
Channel setting	Coefficient	START key	
	Unit	Interval measurement, Comparator measurement	
	Decimal point	LAN, USB, RS-232C	
	Offset	± (0.00000~200000)	
	Sensor mode	με, mV, °C, kgf, mm etc.,	
		Decimal point display can be set to 0 to 5 optional digits	
		Writing for each arbitrary measurement channel	
		Set the type of sensor to be connected	
Quarter bridge 3-wire 120/240/350Ω			
Check function	During measurement	Strain measurement	
	Sensor	Quarter bridge 4-wire 120/240/350Ω	
		Half bridge common dummy, Half bridge measurement Full bridge, Full bridge constant current 350Ω	
	Display setting list	Voltage 300mV, 30V	
		Temperature Thermocouple T, K, J, B, S, R, E, N	
Check function	Sensor	Open check	
		Insulation check, sensitivity check, variation check, thermocouple disconnection check, lead wire resistance check, bridge output check, coefficient check	
	Display setting list	Initial value, lead wire resistance	

*Quarter bridge 4-wire is available only for SSW-50D. (As of February 2024)

Interval measurement

Function	Recording of measurement values at set time interval and time
Time interval	Hours, minutes, seconds, up to 99 hours 59 minutes 59 seconds Can be set for each step
Real time start	Start time (hour, minute, seconds) can be set for each step
Number of start	Up to 9999 times per step or infinite
Number of steps	Programmable up to 10 steps
GOTO step	Program loop possible to one of the previous steps
GOTO comparator	Go to step 1 of the comparator
Sleep function	Automatically turns power on and off at intervals of 1 minute or more between the end of a scan and the start of the next scan

Comparator measurement

Function	Automatic measurement by the amount of change in the setting of any channel (one point)
Comparative amount	Up to ±999999 settable per step
Comparison method	Upper/lower limits, relative values
Number of start	Up to 9999 times per step or infinite
Number of steps	Programmable up to 10 steps
GOTO step	Program loop possible to one of the previous steps
GOTO interval	Go to step 1 of the interval

Time

Setting	Year, month, day, hour, minute, seconds
Accuracy	Daily error: ± 1 seconds (@23°C ± 5°C)
Retention	Approx. 30 days (with full charge)

Display and Operation

Display	Display unit	LCD panel	3.0 semi-transmissive monochrome STN LED backlight
		Resolution	255×160 dots
		Point defect	10 dots or less (excluding aging deterioration)
Operation		POWER, START, ESC, ENT, 0 to 9, F1, F2, F3	

Recording

Built-in	Function	Recording and reproduction of measurement data Saving of setting file
	Recording format	CSV format, TDS format
	Capacity	16 GB
SD card	Function	Recording, reproduction, copying of measurement data Saving of setting file
	Physical format	FAT32
	Recording format	CSV format, TDS format
	Capacity	16 GB (Designated by us)

Interface

LAN	10BASE-T/100BASE-TX General-purpose command port server function (various settings, measurement, data collection)
USB	USB 2.0 protocol compatible Various settings, measurements, data collection
RS-232C	RS-232C compliant Baud rate 9600, 38400, 115200 bps Various settings, measurements, data collection

Power supply

Power supply voltage	DC9~18V50/60Hz
----------------------	----------------

Environment

Operating temperature/humidity range	-10~+50°C 85%RH or less (No condensation)
--------------------------------------	---

Others

External dimensions	280(W)×45(H)×80(D)mm (Excluding rubber protectors and protrusions)
weight	Approx. 800g

Standard accessories

instruction manual for standard accessories(CD)	1
SD card	1
Phillips screwdriver	1
Warranty card	1 copy

Options

SD card	16 GB (Designated by us)
AC adapter	CR-1867
RS-232C Cable	CR-5360
USB cable	Type C USB Cable
External Printer	DPU-S245 (RS-232C connection)

Specification 仕様

T-ZACCS+

Driver unit AU-50MA



Measurement capability

Number of measurement points	When using box connection	Up to 1000 points
	When using box connection and built-in measurement unit together	
Channel unit connection		
Data update cycle		0.080 sec/point (50Hz) 0.067 sec/point (60Hz)
Measurement Mode		Direct
Strain measurement	Applicable wiring methods, gauge resistance	Quarter bridge 3-wire 120/240/350Ω
		Half bridge 120~1000Ω
		Half bridge common dummy 120~1000Ω
		Full bridge 120~1000Ω
		Full bridge constant current 350Ω
	Sensor cable extension range	Full bridge constant current 350Ω Total cable resistance: 400 Ω or less
	Sensitivity change	Full bridge constant current 350Ω +0.1% to -0.5% for total cable resistance 100 Ω
	Lead wire resistance compensation range CometB(1G3W)	Gauge resistance 120Ω : About 100Ω or less Gauge resistance 240Ω : About 200Ω or less Gauge resistance 350Ω : About 300Ω or less
	Zero stability	±1.0×10 ⁻⁶ strain/°C or less (quarter bridge) ±0.5×10 ⁻⁶ strain/°C or less (half bridge)
	Initial unbalance	±750×10 ⁻⁶ strain or less (quarter bridge 3-wire) ±500×10 ⁻⁶ strain or less (half bridge)
DC voltage measurement	Input impedance	1MΩ or more
	Allowable input voltage between B and D	DC±50V MAX
Thermocouple temperature measurements		T, K, J, B, S, R, E, N JIS C1602:2015 IEC60584-1:2013
Check function	During measurement	Open check
	sensor	Insulation check, sensitivity check, variation check, thermocouple disconnection check, lead wire resistance check, bridge output check

Strain measurement

Bridge power supply	DC2V 24ms(50Hz)	
Initial value storage range	±160000×10 ⁻⁶ strain	
Temperature coefficient of accuracy	±0.002% rdg/°C	
Aging change of accuracy	±0.02% rdg/year	
Measuring range and resolution	Measuring range	Resolution
	± 30000×10 ⁻⁶ strain	1×10 ⁻⁶ strain
	±300000×10 ⁻⁶ strain	10×10 ⁻⁶ strain
Accuracy(@23°C±5°C) (Except quarter bridge 4-wire)	±(0.08%rdg+1 digit)	
Accuracy(@23°C±5°C) Quarter bridge 4-wire	±(0.28%rdg+1 digit)	

Constant current strain measurement(Full bridge)

Bridge Power Supply	DC6mA 24ms(50Hz)	
Bridge resistance	350Ω	
Initial value storage range	±160000×10 ⁻⁶ strain	
Temperature coefficient of accuracy	±0.002%rdg/°C	
Aging change of accuracy	±0.02%rdg/year	
Measuring range and resolution	Measuring range	Resolution
	± 30000×10 ⁻⁶ strain	1×10 ⁻⁶ strain
	±300000×10 ⁻⁶ strain	10×10 ⁻⁶ strain
Accuracy (@23°C±5°C)	±(0.08%rdg+3digit)	

DC voltage measurement

Initial value storage range		
V1/1	±160.000mV	
V1/100	±16.0000V	
Temperature coefficient of accuracy	±0.0024%rdg/°C	
Aging change of accuracy	±0.024%rdg/year	
Measuring range and resolution	V1/1	Measuring range
		Resolution
	V1/100	± 30.000mV 0.001mV
		±300.000mV 0.010mV
Accuracy (@23°C±5°C)	V1/1	±(0.08%rdg+3digit)
	V1/100	±(0.08%rdg+2digit)

Thermocouple measurement accuracy

Type	Measuring range	Resolution	Accuracy (@23°C±5°C)	
			External reference junction	Internal reference junction
T	-250~-200°C	0.1°C	±(0.38%rdg+0.6°C)	±(0.38%rdg+3.9°C)
	-200~-100°C	0.1°C	±(0.15%rdg+0.2°C)	±(0.15%rdg+1.4°C)
	-100~-+400°C	0.1°C	±(0.10%rdg+0.2°C)	±(0.10%rdg+0.8°C)
K	-210~-160°C	0.1°C	±(0.19%rdg+0.3°C)	±(0.19%rdg+1.6°C)
	-160~0°C	0.1°C	±(0.12%rdg+0.2°C)	±(0.12%rdg+1.0°C)
	0~+960°C	0.1°C	±(0.08%rdg+0.1°C)	±(0.08%rdg+0.5°C)
J	+960~+1370°C	0.1°C	±(0.10%rdg+0.9°C)	±(0.10%rdg+1.4°C)
	-200~-160°C	0.1°C	±(0.16%rdg+0.2°C)	±(0.16%rdg+1.2°C)
	-160~0°C	0.1°C	±(0.12%rdg+0.1°C)	±(0.12%rdg+0.8°C)
B	0~+700°C	0.1°C	±(0.08%rdg+0.1°C)	±(0.08%rdg+0.5°C)
	+700~+1200°C	0.1°C	±(0.08%rdg+0.6°C)	±(0.08%rdg+0.9°C)
	+200~+280°C	0.5~0.4°C	±(0.04%rdg+4.0°C)	±(0.04%rdg+4.0°C)
S	+280~+800°C	0.3~0.1°C	±(0.04%rdg+1.2°C)	±(0.04%rdg+1.2°C)
	+800~+1760°C	0.1°C	±(0.05%rdg+0.4°C)	±(0.05%rdg+0.4°C)
	-10~+200°C	0.1°C	±(0.09%rdg+0.6°C)	±(0.09%rdg+1.2°C)
R	+200~+1760°C	0.1°C	±(0.07%rdg+0.4°C)	±(0.07%rdg+0.7°C)
	-10~+150°C	0.1°C	±(0.09%rdg+0.7°C)	±(0.09%rdg+1.2°C)
	+150~+1760°C	0.1°C	±(0.07%rdg+0.4°C)	±(0.07%rdg+0.7°C)
E	-210~+550°C	0.1°C	±(0.17%rdg+0.2°C)	±(0.17%rdg+1.4°C)
	+550~+1000°C	0.1°C	±(0.09%rdg+0.4°C)	±(0.09%rdg+0.8°C)
	-200~0°C	0.1°C	±(0.18%rdg+0.4°C)	±(0.18%rdg+1.6°C)
N	0~+1090°C	0.1°C	±(0.08%rdg+0.2°C)	±(0.08%rdg+0.6°C)
	+1090~+1300°C	0.1°C	±(0.08%rdg+0.9°C)	±(0.08%rdg+1.2°C)

*The accuracy of sensor is not included, and thermocouple B does not use a reference junction

Switching box drive unit

Compatible model		SSW-50D, ASW-50C AU-50M
No. of units connected	Without booster power	8 units connected, 400 points
	Booster power available	20 units connected, 1000 points
Extension distance	Without booster power	120m
	Booster power available	2km
Connection cable		Switch box cable (CR-65) or switching box extension cable (CR-800)

Compatible model		NSW series/TML-NET compatible transducers
No. of units connected	Low consumption type	Up to 100 units
	Existing type	Up to 20 units (150m or less)
Extension distance	Low consumption type	2km
	Existing type	Within 1 km (10 units or less)
Connection cable		Dedicated 2-conductor shielded cable

Channel unit connection

Compatible model	AU-10/AU-10-05
No. of units connected	Up to 5 units
Connectors	Dedicated connector for unit connection

Power

Supply power	Supplied by TS-360
--------------	--------------------

Environment

Operating temperature/humidity range	-10~ +50°C 85% RH or less (excluding condensation)
--------------------------------------	--

Other

External dimensions	280(W)×45(H)×60(D)mm (Excluding rubber protectors and protrusions)
Weight	Approx. 800g

Standard accessories

Warranty card	1 copy
---------------	--------

T-ZACCS 3 Specification 仕様

T-ZACCS UNIT

Channel unit AU-10/AU-10-05



Function

Number of measuring point	10
input terminal	Dual-use screw and solder type
One-touch connector	NDIS One-touch connector(AU-10-05 only)
Measuring capacity	Equivalent to AU-50MA/AU-50M

Power

Supply power	Supplied by AU-50MA/AU-50M
--------------	----------------------------

Environment

Operating temperature/humidity range	-10~+50°C 85% RH or less (excluding condensation)
--------------------------------------	---

Other

External dimensions	AU-10	280 (W)×45 (H)×60 (D) mm
	AU-10-05	280 (W)×45 (H)×80 (D) mm (Excluding rubber protector and projection)
Weight	AU-10	Approx. 900g
	AU-10-05	Approx. 1.2kg

Standard accessories

Warranty card	1 copy
---------------	--------

T-ZACCS+

Battery unit BA-360



Function

Function	Ability to run TS-360 on a single battery
Batteries	4 single alkaline dry cells
Usable time	Continuous usage : Approx. 40 hours
	At 1-hour interval : Approx. 8 months (10 channels, scan, sleep on, 23±5°C)

Environment

Operating temperature/humidity range	-10~+50°C 85% RH or less (excluding condensation)
--------------------------------------	---

Other

External dimensions	280 (W)×60 (H)×60 (D) mm (Excluding rubber protector and projection)
Weight	Approx. 1.2 kg (including 4 single dry cells)

Standard accessories

Single alkaline dry cell	4
Warranty card	1 copy

Expandable by unit! 「T-ZACCS BOX AU-50」

The AU-50 consists of a master unit and a channel unit.

It can be used with TS-360, TDS-540, etc. and can be mixed with conventional switchboxes ASW-50C/SSW-50D.

1 to 5 channel units can be added
to the Master unit

T-ZACCS+

Master unit AU-50M

T-ZACCS UNIT

Channel unit AU-10/AU-10-05



Approval Certificate **ISO9001**
Design and manufacture of
strain gauges, strain measuring
equipment and transducers

The contents of this catalog are subject to change without prior notice.
The contents of this catalog are as of October 2024. TML Pam E3021D.



8-2, Minami-ohi 6-chome, Shinagawa-ku, Tokyo 140-8560, JAPAN
TEL: +81-3-3763-5614 FAX: +81-3-3763-6128

